

Part No. 41006

## DISPLAYPORT 1.2 TO VGA ACTIVE CONVERTER

CONNECTS A DISPLAYPORT SOURCE TO A VGA MONITOR



### DESCRIPTION

- Converts a DisplayPort signal into VGA
- Supports resolutions up to 1920x1080@60Hz
- Add a VGA monitor as a secondary display
- Quick and simple Plug & Play installation
- 2 year warranty

The Lindy DisplayPort 1.2 to VGA Converter is ideal for connecting a DisplayPort equipped source such as a PC or laptop to a VGA monitor. It supports high definition video resolutions up to 1920x1080@60Hz. Active conversion ensures compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage.

The converter can also be used to add another display to extend the available desktop workspace and increase productivity. Internal copper shielding provides enhanced reliability and compatibility. The converter is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug & Play installation.

### RELATED PRODUCTS

0

# DISPLAYPORT 1.2 TO VGA ACTIVE CONVERTER

## SPECIFICATIONS

|                    |                      |
|--------------------|----------------------|
| AV Interface       | DisplayPort to VGA   |
| Interface Standard | DisplayPort 1.2, VGA |

|                          |                |
|--------------------------|----------------|
| Supported Bandwidth      | 10.8Gbps       |
| Maximum Input Resolution | 1920x1080@60Hz |

|                           |                |
|---------------------------|----------------|
| Maximum Output Resolution | 1920x1080@60Hz |
|---------------------------|----------------|

|         |         |
|---------|---------|
| Chipset | ANX9833 |
|---------|---------|

|                 |   |
|-----------------|---|
| HDCP Support    | - |
| Supported Audio | - |

|                      |   |
|----------------------|---|
| Separate Audio Ports | - |
| Special Features     | - |

## PHYSICAL PROPERTIES

|                            |   |
|----------------------------|---|
| Dimensions (approx.) WxDxH | 38x61x17mm<br>[1.5x2.4x0.67in]<br>20x36x11mm<br>[0.79x1.42x0.43in]/DP |
|----------------------------|---|

|              |                |
|--------------|----------------|
| Cable Length | 150mm [5.91in] |
|--------------|----------------|

|                       |                              |
|-----------------------|------------------------------|
| Housing Material      | TPE                          |
| Jacket Material       | PVC                          |
| Jacket Diameter       | 6.5mm [0.26in]               |
| Minimum Bend Radius   | 70mm [2.76in]                |
| Net Weight            | 0.045kg [0.1lb]              |
| Operating Temperature | -20°C - 80°C [-4°F - 176°F]  |
| Storage Temperature   | -20°C - 70°C [-4°F - 158°F]  |
| Humidity              | 20 - 90% RH (non-condensing) |
| Colour                | Black                        |

## CONNECTORS

|       |                  |
|-------|------------------|
| Input | DisplayPort Male |
|-------|------------------|

|        |            |
|--------|------------|
| Output | VGA Female |
|--------|------------|

## MISCELLANEOUS

|                     |                               |
|---------------------|-------------------------------|
| Packaging Type      | Polybag                       |
| Packaging Dimension | 160x160x20mm [6.3x6.3x0.79in] |
| Gross Weight        | 0.049kg [0.011lb]             |
| Warranty (Years)    | 2                             |
| Certificated        | CE, FCC, RoHS & REACH         |

## PURCHASING INFORMATION

|     |               |
|-----|---------------|
| No. | 41006         |
| EAN | 4002888410069 |

## PACKAGING CONTENTS

DisplayPort 1.2 to VGA Active Converter