Cabo USB 2.0 A-A 05.00m LINDY (36695)

Referencia : 36695

Cabo USB 2.0 A-A 05.00m LINDY (36695)

Fabricante : Lindy

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A to A cables are the professional choice for high performance connections in commercial AV and IT installations.

• Professional choice USB 2.0 Type A to A cable for commercial and high performance AV and IT installations
• Supports data transfer speeds up to 480Mbps
• Robust PVC housing, nickel connectors and gold plated contacts
• Double shielded cable, corrosion resistant tinned copper conductors
• USB 2.0, 480Mbps

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel connectors maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Technical details

• Connectors

• Connector A: USB 2.0 Type A Male
• Connector B: USB 2.0 Type A Male
• Housing Material: PVC
• Connector Plating: Nickel
• Pin Construction: Copper
• Pin Plating: Gold
• Dimensions (approx.) WxDxH: 15.5x35x7.8mm (0.61x1.38x0.31in)

• Cable Construction

• Length: 5m
• Standard: USB 2.0
• Colour: Black
• Type: Round
• Jacket Diameter: 4.4mm (0.17in)

LIDERTRÃ“NICA - Um Mundo de AcessÃ³rios de InformÃ¡tica

Cabo USB 2.0 A-A 05.00m LINDY (36695)

LIDERTRÃ“NICA - Um Mundo de Acessórios para InformÃ¡tica

• Jacket Material: PVC
• Conductor Material: Tinned Copper
• Conductor Gauge: 26/28AWG
• Shielding: Aluminium Magnesium Braid

• Specifications

• Supported Bandwidth: 480Mbps
• Maximum Resolution: -
• Nominal Attenuation: 5.8db/km
• Minumum Band Radius: 16mm (0.63in)
• Operating Temperature: 0Â°C - 60Â°C (32Â°F - 140Â°F)
• Storage Temperature: 0Â°C - 60Â°C (32Â°F - 140Â°F)
• ATC Approved: -

• Miscellaneous

• Packaging Type: Polybag
• Certificated: RoHS, REACH & UL

style="width: 17px; height: 17px;" alt="seta"

Para
ver a lista de todos os CABOS USB, clique
style="font-weight: bold; color: rgb(204, 0, 0);"
href="index.php?cPath=47_91"
target="_top">AQUI
style="color: rgb(204, 0, 0);">.

style="width: 17px; height: 17px;" alt="seta"

Para
ver a lista de todos os ADAPTADORES, clique
style="font-weight: bold; color: rgb(0, 153, 0);"
href="index.php?cPath=49_65"
target="_top">AQUI
style="color: rgb(0, 153, 0);">.

style="width: 17px; height: 17px;" alt="seta"

Para
ver a lista de todos os CONVERSORES USB, clique
style="font-weight: bold; color: rgb(51, 51, 255);"
href="index.php?cPath=21_27"

Cabo USB 2.0 A-A 05.00m LINDY (36695)

target="_top">AQUI
style="color: rgb(51, 51, 255);">.

style="width: 17px; height: 17px;" alt="seta"

Para
ver a lista de todos os CABOS, clique
style="font-weight: bold; color: rgb(153, 51, 153);"
href="index.php?cPath=47â€•
target="_top">AQUI
style="color: rgb(153, 51, 153);">.

A conexÃ£o USB permite a ligaÃ§Ã£o de perifÃ©ricos, sem a necessidade de desligar o computador. Actualmente, Ã© talvez o tipo de ligaÃ§Ã£o mais usada, ligando desde impressoras, ratos e teclados, mÃ¡quinas industriais, entre outros.
Hoje em dia sÃ³ se fabricam perifÃ©ricos e cabos USB 2.0, no entanto tambÃ©m existem 1.1, um tipo de ligaÃ§Ã£o mais antiga e com menos velocidade, mas perfeitamente compatÃ-vel com 2.0.
O tipo de fichas mais comum Ã© o A e B, A no computador e B numa impressora por exemplo. No entanto, tambÃ©m existem algumas variaÃ§Ãµes destas ligaÃ§Ãµes, como Macho e FÃªmea nas extensÃµes, e os Mini USBs para ligar mÃ¡quinas fotogrÃ¡ficas.
O mÃ¡ximo de comprimento de cabo que o USB permite sÃ£o 5 metros. A partir deste ponto implica uma perda de sinal, chegando mesmo a extinguir-se. Para contornar este problema, o ideal Ã© a utilizaÃ§Ã£o de extensÃµes amplificadas, pois as mesmas possuem um amplificador na ponta que dÃ¡ um novo impulso ao sinal.

LIDERTRÃ“NICA - Um Mundo de Acessórios para InformÃ¡tica

Este artigo foi introduzido no catalogo online : Saturday, 13 April 2013