

> USB 3.2 Gen 2x2 Dual M.2 NVMe SSD & Clone LINDY (43382)

## USB 3.2 Gen 2x2 Dual M.2 NVMe SSD & Clone LINDY (43382)



Referencia : 43382

USB 3.2 Gen 2x2 Dual M.2 NVMe SSD & Clone LINDY (43382)

Fabricante : Lindy

Easy and fast access to and cloning of M.2 NVMe SSDs

- Aluminium Enclosure with USB Type C interface for two PCIe/NVMe based M.2 SSDs (not included)
- Allows access to and/or duplication of M.2 NVMe SSDs - even without connection to a host computer ( Offline Cloning )
- USB 3.2 Gen 2x2 standard with SuperSpeed USB 20Gbps data transfer rates\*
- With ultra-thin

The Lindy USB 3.2 Dual M.2 NVMe SSD Enclosure allows the user to install two PCIe/NVMe based M.2 SSDs as an external drive to USB hosts like laptops or PCs. The additional Clone feature enables duplicating M.2 NVMe SSDs - even without connection to a computer ( offline cloning ). Support for the USB 3.2 Gen 2x2 standard guarantees SuperSpeed 20Gbps data transfer rates. UASP support also ensures faster speeds for UASP enabled computers.

This Lindy enclosure is compatible with PCIe/NVMe based M.2 SSDs with M key in 42, 60 and 80mm lengths. The tool-free design makes installation very easy. An included external power adapter guarantees safe power supply.

Please note that that 20Gbps full support is only possible with a USB 3.2 2x2 host controller.

### • Specifications

- Interface: USB to 2x PCIe/NVMe M.2 SSD
- Interface Standard: USB 3.2 Gen 2x2, PCIe 3.0 x2
- Supported Bandwidth: 20Gbps (USB), 32Gbps - each up to 16Gbps (PCI 3.0 x2)
- Chipset: JMS586U
- Compatibility: USB Type C equipped computers
- Special Features: supports 42/60/80mm SSDs, UASP & TRIM, LED indicator for Clone process

### • Connectors

> USB 3.2 Gen 2x2 Dual M.2 NVMe SSD & Clone LINDY (43382)

## USB 3.2 Gen 2x2 Dual M.2 NVMe SSD & Clone LINDY (43382)

- Inputs: 1 x USB Type C (Female)
- Outputs: 2 x PCIe based M.2 (Female), M key and B+M key
- Power: 5.5/2.5mm DC socket

### • Connectors

- Dimensions WxDxH: 143x77x17.5mm (5.63x3.03x0.69in)
- Cable Length: 0.25m (0.82ft)
- Housing Material: Aluminium and ABS
- Net Weight: 0.174kg (0.38lb)
- Operating Temperature: 5Â°C - 35Â°C (41Â°F - 95Â°F)
- Storage Temperature: -10Â°C - 90Â°C (-14Â°F - 122Â°F)
- Humidity: 10 - 90% RH (non-condensing)
- Power Requirements: 12VDC 2A
- Colour: Silver

### • Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 160x100x110mm (6.30x3.94x4.33in)
- Gross Weight: 0.47kg (1.04lb)
- Product Compliance: CE, FCC, RoHS & REACH, CP65

### • Package Contents

- USB 3.2 Dual M.2 NVMe SSD Enclosure
- 0.25m USB 3.2 Gen 2x2 Type C to C cable
- Multi-Country Power Supply 12VDC 2A with country adapters (EU, UK; US, AUS)
- 2x thermal conductive pad
- 2x thermal conductive plate
- 4x M.2 rubber retainer
- Lindy Manual

Manual de Instruções (PDF 112.80KB)

Este artigo foi introduzido no catalogo online : Wednesday, 07 May 2025