USB 3.1 Type C Hub 7 Port Metal LINDY (43275)

Referencia : 43275

USB 3.1 Type C Hub 7 Port Metal LINDY (43275)

Fabricante : Lindy

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

• Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
• Hard-wearing USB Hub - Perfect for industrial applications
• Robust metal housing with high EMC protection and integrated brackets for mounting
• Powered by external power supply or terminal block

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

Manual de InstruÃ§Ãµes (PDF)

Technical details

• Specifications

• USB Standard: USB 3.1 Gen 2
• Supported Bandwidth: 10Gbps
• Chipset: 2x VL820
• Compatibility: USB Type C equipped computers, Thunderbolt 3
• Special Features: Integrated brackets for mounting; allows

LIDERTRÃ“NICA - Um Mundo de Acessórios para InformÃ¡tica

USB 3.1 Type C Hub 7 Port Metal LINDY (43275)

connection of USB Type C locking cables; Terminal Block

• Connectors

• Inputs: 1 x USB Type C (Female)
• Outputs: 3 x USB Type C (Female), 4 x USB Type A (Female)
• Power: DC screw connector

• Physical Properties

• Dimensions WxDxH: 184.5x64.3x20mm (7.26x2.53x0.79in)
• Housing Material: Metal
• Net Weight: 0.3kg (0.66lb)
• Operating Temperature: 0Â°C - 50Â°C (32Â°F -122Â°F)
• Storage Temperature: -20Â°C - 60Â°C (-4Â°F -140Â°F)
• Humidity: 90% RH (non-condensing)
• Power Requirements: 16VDC 3A
• Colour: Black

• Miscellaneous

• Packaging Type: Carton Box
• Packaging Dimensions: 260x180x70mm (10.24x7.09x2.76in)
• Gross Weight: 0.844kg (1.86lb)
• Certificated: CE, FCC, RoHS, REACH, California Proposition 65

• Package Contents

• 7 Port USB 3.1 Gen 2 Metal Hub
• 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
• Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
• Lindy Manual

LIDERTRÃ“NICA - Um Mundo de Acessórios para Informática!