

KVM > KVM Docking Station MST Type C - 2 Ports LINDY (43202)

KVM Docking Station MST Type C - 2 Ports LINDY (43202)

Referencia : 43202

KVM Docking Station MST Type C - 2 Ports LINDY (43202)

Fabricante : Lindy



The Lindy 2 Port Type C MST KVM Docking Station is a compact and versatile solution for connecting laptops to a range of interfaces including two displays. Featuring all critical interfaces required for a modern workstation, this device combines the comfort of a Desktop Docking Station with a Type C KVM Switch; it provides two USB 3.2 Type C inputs to connect sources such as laptops, tablets or smartphones in order to share the same workstation and peripherals connected. Switching is easily possible by pushing the button on the top of the unit.

- Adds DP, HDMI, USB Type A, USB Type C, Gigabit Ethernet, Audio and a Power Delivery ports to 2 laptops, tablets or smartphones
- Supports up to 4K60 for one display, 4K30 and Full HD for dual display (MST)
- Features DisplayPort Alternate Mode
- USB Power Delivery 3.0 (100W on port 1 and 65W on port 2) allows charging the laptop while using the Docking Station

The Docking Station enables the connection of two displays via HDMI and DisplayPort outputs at resolutions of 3840x2160@60Hz using DisplayPort Alternate Mode through the USB Type C ports. It supports also MST function to manage the simultaneous connection of both monitors, one with 4K30 and one with 1920x1080@60Hz maximum resolutions.

The USB Type C and Type A ports on the front panel provide up to 5Gbps of data transfer and BC 1.2 for fast charging perfect for connecting peripherals such as a hard drive, webcam and for charging a mobile device. Both USB Type C inputs support USB Power Delivery 3.0, PC1 port up to 100W (connecting an additional Type C PD power supply to PD port) while PC2 port up to 65W (just connecting the included power supply).

It provides also a Gigabit Ethernet and a 3.5mm port to connect a Network and an Audio stereo input/output device such as headphones, speakers or microphone.

KVM > KVM Docking Station MST Type C - 2 Ports LINDY (43202)

KVM Docking Station MST Type C - 2 Ports LINDY (43202)

Manual de Instruções (PDF)

Technical Information

• Specifications

- Interface: USB Type C to HDMI, DP, RJ45, USB Type A, USB Type C, 3.5mm
- Interface Standard: USB 3.2 / 3.1 Gen 1 / USB 3.0, HDMI 2.0, Gigabit LAN, DisplayPort 1.4
- Supported Bandwidth: 18G, 5Gbps, 10/100/1000Mbps
- Maximum Input Resolution: 3840x2160@60Hz
- Maximum Output Resolution: 3840x2160@60Hz
- Chipset: VL170 / VL160, FL7102 / FL7112, AX88179A, GL3510, KT0200, RTD2142
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: PD 3.0 up to 100W on port 1 and up to 65W on port 2
- HDCP Support: HDCP 1.4/2.2
- Supported Audio: 24/96kHz audio sampling rate
- Separate Audio Ports: 1x Audio combo port 3.5mm
- Special Features: MST, DisplayPort Alternate Mode, BC 1.2 charging

• Connectors

- Inputs: 2 x USB Type C (Female)
- Outputs: 1 x HDMI (Female), 1 x DisplayPort (Female), 1 x RJ45 (Female), 3 x USB Type A (Female), 3 x USB Type C (1 for PD) (Female), 1 x 3.5mm (Female)
- Power: 5.5/2.5mm

• Physical Properties

- Dimensions WxDxH: 185x79x28.7mm (7.28x3.11x1.13in)
- Housing Material: Plastic and Aluminium
- Net Weight: 0.926kg (2.04lb)
- Operating Temperature: 0°C - 55°C (32°F - 131°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)
- Humidity: 0 - 85% RH (non-condensing)
- Power Requirements: 24VDC 5.63A
- Colour: Black

• Miscellaneous

- Packaging Type: Carton Box

KVM > KVM Docking Station MST Type C - 2 Ports LINDY (43202)

KVM Docking Station MST Type C - 2 Ports LINDY (43202)

- Packaging Dimensions: 250x203x50mm (9.84x7.99x1.97in)
- Gross Weight: 1.079kg (2.38lb)
- Certificated: CE, UKCA, FCC, REACH & RoHS, CP65

- Package Contents

- 2 Port Type C MST KVM Docking Station
- 2 x Mains Cable IEC C13 (Schuko and UK), 1m
- IEC C14 Power Supply
- Lindy Manual

Este artigo foi introduzido no catalogo online : Monday, 29 August 2022