

> Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)



Referencia : 30112

Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

Fabricante : Lindy

Quickly recharge your E-Vehicle or Plug in Hybrid with the Lindy Type 2 cables. With this charging cable you can recharge any vehicle, fitted with a Type 2 port, at a public charging station or wall box. As Type 2 is standard in the EU, you can use this cable at most charging stations in the European area. 3-phase charging with up to 22kW (32A 480VAC) is possible as well as 1-phase charging.

- Type 2 to Type 2 cable to charge any Type 2 fitted vehicles at a public charging station or wall box
- 3-phase charging with max. 22kW charging power for faster charging
- Robust TPU jacket and PVC connectors with rubber covers to protect the connectors when not in use
- Supplied with a carrying bag for convenient storage

The cable is well protected against dust and water (IP55), it is UV-resistant and the connectors are flame retardant (UL 94 V-0). The plugs are designed for more than 10,000 mating cycles, which means a lifespan of more than 10 years with daily use.

When not in use the cable can easily be stored in the carrying bag which is supplied with the product.

This product has been certified by TÜV Rheinland.

[CE Declaration](#)

[DataSheet](#)

[Technical Details](#)

> Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

- Connectors

- Connector A: Type 2 Female (IEC 62196)
- Connector B: Type 2 Male (IEC 62196)
- Housing Material: PC & Nylon
- Dimensions (approx.) WxDxH:
 - Type 2 Female: 204.2x122.3x71mm (8.04x4.81x2.8in)
 - Type 2 Male: 214.1x115.5x56mm (8.43x4.55x2.2in)

- Cable Construction

- Length: 5m
- Colour: Black
- Charging Mode: Mode 3
- Number of Phases: 3
- Jacket Diameter: 16.8mm (0.66in)
- Jacket Material: TPU
- Conductor Material: Copper alloy with silver plating

- Specifications

- Rated Current: 32A
- Operation Voltage: 480V
- Charging Power: 22kW
- Minimum Bend Radius: 84mm (3.31in)
- Protection Level: IP55, IP65 (with protection caps)
- UV Resistant: Yes
- Flame Retardant Grade: UL 94 V-0 (connectors only)
- Operating Temperature: -30°C - 50°C (-22°F - 122°F)
- Storage Temperature: -30°C - 40°C (-22°F - 104°F)

- Miscellaneous

- Packaging Type: Carton Box
- Product Compliance: CE, UKCA, RoHS, REACH, T&E

- Package Contents

- 5m Type 2 Charging Cable, 11kW
- Carrying bag

> Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

Cabo EV-Charging Type 2 22kW 05.0m LINDY (30112)

Este artigo foi introduzido no catalogo online : Friday, 24 March 2023

LIDERTRONICA - Um Mundo de Acessórios para Informática