

HDMI > Emulador EDID/DDC > HDMI 8k EDID Emulator LINDY (32119)

## HDMI 8k EDID Emulator LINDY (32119)



Referencia : 32119

HDMI 8k EDID Emulator LINDY (32119)

Fabricante : Lindy

Continuously emulates HDMI® EDID information

- Supports resolutions up to 7680x4320@60Hz or 3840x2160@120Hz with additional support for HDR
- Uses Cloned Data or Pre-stored resolutions/timings
- Headless connection (No monitor connection required)

The Lindy HDMI® 8K60 EDID Emulator Adapter is designed for systems that require an uninterrupted signal to overcome EDID related issues that commonly occur when using AV equipment such as KVM's, Extenders, Splitters & Switches. With the small-scale and minimalistic design, this is a handy connectivity solution for both AV and IT installers to ensure legacy and new HDMI equipment works seamlessly with no compromise on performance.

The Emulator also features LED indicators to ensure a quick simple installation process and with support for resolutions up to 7680x4320@60Hz or 3840x2160@120Hz HDR (Via cloning), HDCP 2.3 pass-through, this emulator is perfect for use with Ultra HD 4K monitors.

This adapter can be used to quickly and easily clone the EDID data from the HDMI® display so that the graphics card has direct access to the correct data from the display, the cloning process takes less than 10 seconds; Alternatively the EDID Emulator is configured with a preset EDID which uses the most common resolutions/timing combinations. Please see the technical information section for a full breakdown.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

- Miscellaneous

HDMI > Emulador EDID/DDC > HDMI 8k EDID Emulator LINDY (32119)

## HDMI 8k EDID Emulator LINDY (32119)

- AV Interface: HDMI®
- Interface Standard: 2.1
- Supported Bandwidth: 48Gbps
- Maximum Resolution: 7680x4320@60Hz 4:4:4 10Bit
- Video EDID:
  - 640x480 at 60/67/72/75Hz
  - 720x400 at 70Hz
  - 720x480 at 60Hz
  - 720x576 at 50Hz
  - 720x576i at 50Hz
  - 800x600 at 60/72/75Hz
  - 832x624 at 75Hz
  - 1024x768 at 60/70/75Hz
  - 1152x870 at 75Hz
  - 1152x864 at 75Hz
  - 1280x720 at 50/60Hz
  - 1280x800 at 60Hz
  - 1280x1024 at 60/75Hz
  - 1440x900 at 60Hz
  - 1600x900 at 60Hz
  - 1680x1050 at 60Hz
  - 1920x1080i at 50/60Hz
  - 1920x1080 at 24/50/60/120Hz (default Resolution)
  - 2560x1440 at 60Hz
  - 3840x2160Hz at 24/30/50/60/100/120Hz
  - 4096x2160 at 24/30/50/60/100/120Hz
- Audio EDID: LPCM 2-Channel, 16/20/24 bit depth at 32/44.1/48 kHz
- HDCP Support: HDCP 2.3
- Special Features: Headless connection (No Monitor connection required)

### • Connectors

- Input: HDMI® Male
- Output: HDMI® Female
- Power: Via HDMI® source Interface

### • Physical Properties

- Dimensions WxDxH: 24.14x44.18x11.84mm (0.95x1.73x0.46in)
- Housing Material: ABS
- Net Weight: 0.0088kg (0.0194lb)
- Operating Temperature: 0°C - 60°C (°F - °F)
- Storage Temperature: -10°C - 80°C (°F - °F)
- Humidity: 0-80% RH (non-condensing)
- Colour: Black

HDMI > Emulador EDID/DDC > HDMI 8k EDID Emulator LINDY (32119)

## HDMI 8k EDID Emulator LINDY (32119)

- Miscellaneous
  - Packaging Type: Polybag
  - Packaging Dimensions: 133x144mm (5.23x5.66in)
  - Gross Weight: 0.022kg (0.048lb)
  - Product Compliance: CE, FCC, RoHS & REACH

- Package Contents

- EDID Emulator
- Lindy Manual

Manual de Instruções (PDF 112.80KB)

---

Este artigo foi introduzido no catalogo online : Thursday, 05 March 2026