

> Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)



Referencia : 36666

Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

Fabricante : Lindy

1.0m USB 3.2 Type C to B Cable, 5Gbps, Anthra Line

USB Type C Male to B Male

- Super-speed data transfer up to 5Gbps, enabling efficient and reliable transfer of large files such as HD videos and backups between devices.
- Delivers up to 4.5W of power (5V 0.9A) to efficiently and safely power connected devices while transferring data.
- Perfect for connecting modern laptops, tablets and desktops with USB-C ports to printers, scanners, and external storage devices equipped with USB Type-B.
- Triple-shielding for enhanced signal integrity and nickel-plated connectors for durable, corrosion-resistant performance.

The Anthra Line USB 3.2 Gen 1x1 Type C to B cables from Lindy are purpose-built for high-performance AV and IT applications. Part of Lindy's professional-grade Cable Lines range, they combine premium materials with advanced engineering for maximum reliability.

Provides 4.5W (5V 0.9A) of power to keep peripherals such as printers, scanners and external devices running smoothly while files are being transferred.

USB 3.2 Gen 1x1 offers super-speed 5Gbps data transfer, making it ideal for transferring HD videos and rapid backups between USB-C hosts and USB Type-B devices.

The robust triple-shielded design with tinned copper conductors and nickel-plated connectors ensures excellent signal quality and strong resistance to EMI/RFI in challenging environments.

• Connectors

- Connector A: USB 3.2 Type C Male
- Connector B: USB 3.2 Type B Male
- Housing Material: PVC
- Shielding in head shell: Copper foil
- Connector Plating: Nickel
- Pin Construction:
- C: High conductivity copper

> Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

- B: Brass
- Pin Plating: Gold
- Dimensions (approx.) WxDxH:
 - C: 10.8x32x7.8mm (0.43x1.26x0.31in)
 - B: 12.2x46x10mm (0.48x1.81x0.39in)
- Cable Construction
 - Jacket Diameter: 4.3mm (0.17in)
 - Jacket Material: PVC
 - Conductor Material: Tinned Copper
 - Conductor Gauge Power: 22AWG
 - Conductor Gauge Data: 30AWG
 - Shielding: Tinned Copper Braid 82%
- Specifications
 - Length: 1.0m (3.28ft)
 - Colour: Black
 - Type: Round
 - Standard: USB 3.2 Gen 1x2
 - Supported Bandwidth: 5Gbps
 - Maximum Power: 4.5W (5V 0.9A)
 - E-Mark: No
 - Maximum Resolution: -
 - Supported Protocols: USB 3.2, USB 2.0
 - Nominal Attenuation: 100-2500MHz < 20dB
 - Minimum Bend Radius: 25mm (0.98in)
 - Operating Temperature: 0°C - 40°C (32°F - 104°F)
 - Storage Temperature: 0°C - 70°C (32°F - 158°F)
- Miscellaneous
 - Packaging Type: Polybag
 - Product Compliance: RoHS, REACH, California Proposition 65, UL (raw cable)
- This product is also available in other lengths
 - 36665 - 0.5m (1.64ft)
 - 36666 - 1m (3.28ft)
 - 36667 - 2m (6.56ft)
 - 36668 - 3m (9.84ft)

> Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

Cabo USB 3.2 Tipo C (m) / B (m) 01.00m LINDY (36666)

Este artigo foi introduzido no catalogo online : Wednesday, 11 March 2026

LIDERTRONICA - Um Mundo de Acessórios para Informática