

> Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)



Referencia : 36956

Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

Fabricante : Lindy

Cabo USB 4 Gen 3x2 Tipo C M/M 0.8m 100W 40Gbps, Anthra Line

The Anthra Line USB4 Gen 3x2 Type C cables from Lindy are purpose-built for high-performance AV and IT applications. Part of Lindy's professional-grade Cable Lines range, they combine premium materials with advanced engineering for maximum reliability.

- Blazing-fast data transfer speeds up to 40Gbps, perfect for ultra-fast file transfers, rapid backups and seamless high-resolution media streaming in demanding professional workflows.
- Delivers up to 240W of power via USB Power Delivery (48V 5A) to rapidly charge laptops, tablets, and smartphones, keeping devices powered throughout demanding workdays.
- Supports video at up to 8K 60Hz via DisplayPort Alternate Mode, enabling ultra high-resolution video output for modern laptops, workstations, and AV systems.
- Industrial-grade construction featuring triple-shielded cable, soft TPE jacket, and gold-plated contacts for superior performance, signal integrity, and durability in mission-critical environments.

An integrated E-Mark chip enables safer 240W (48V 5A) fast charging with USB Power Delivery, allowing for the voltage and current to be automatically adjusted to the needs of connected such as mobile phones, tablets and laptops to prevent overvoltage and overcurrent.

USB4 Gen 3x2 delivers high-speed 40Gbps transfer speeds, doubling the performance of previous USB generations. Whether you're transferring massive design files, editing high-resolution videos directly from external storage, or connecting next-gen peripherals, this standard ensures maximum efficiency and zero bottlenecks.

DisplayPort Alternate Mode enables crisp 4K and 8K video

> Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

output at 60Hz, making them perfect for connecting to ultra-high-resolution displays and AV equipment. The robust coaxial construction with triple shielding, silver plated copper conductors, and nickel-plated connectors ensures excellent signal quality and strong resistance to EMI/RFI in challenging environments.

With reversible USB Type C connectors and full bi-directional communication, these cables guarantee simple, reliable connections every time.

Technical details

• Connectors

- Connector A: USB 4 Type C Male
- Connector B: USB 4 Type C Male
- Housing Material: TPE
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions (approx.) WxDxH: 34.3x12.7x7.3mm (1.35x0.50x0.29in)

• Cable Construction

- Jacket Diameter: 4.8mm (0.19in)
- Jacket Material: TPE
- Conductor Material: Silver plated copper
- Conductor Gauge Power: 23AWG
- Conductor Gauge Data: 30AWG/33AWG/34AWG
- Shielding: Copper Braid 85%

• Specifications

- Length: 0.8m (2.62ft)
- Colour: Black
- Type: Round
- Standard: USB4 Gen 3x2
- Supported Bandwidth: 40Gbps
- Maximum Power: PD 3.1 with ERP up to 240W (48V 5A)
- E-Mark: Yes
- Maximum Resolution: 3840x2160@60Hz, 7680x4320@60Hz

> Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

Cabo USB4 Tipo C 00.8m 5A 100W 40Gbps Gen3x2 LINDY (36956)

- Supported Protocols: USB4, USB 3.2, USB 2.0, Thunderbolt 3, DisplayPort 2.0
- Nominal Attenuation: 0.5Mhz-15Ghz-11dB
- Minimum Bend Radius: 28.8mm (1.13in)
- Operating Temperature: -20Â°C - 40Â°C (-4Â°F - 104Â°F)
- Storage Temperature: -40 Â°C - 80Â°C (-40Â°F - 176Â°F)

- Miscellaneous

- Packaging Type: Polybag
- Certificated: RoHS, REACH, California Proposition 65, UL

- This product is also available in other lengths

- 36956 - 0.8m (2.62ft)
- 36957 - 1.5m (4.92ft)
- 36958 - 2m (6.56ft)

Este artigo foi introduzido no catalogo online : Friday, 20 March 2026