

> Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)

Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)



Referencia : 43503

Cabo USB-C DP 01.0m 8K60 Bi-Directional LINDY (43503)

Fabricante : Lindy

For resolutions up to 7680x4320 @ 60Hz

- - Bi-Directional functionality enables quick and easy switching between a DisplayPort display or a Type C display.
- - Supports UHD resolutions up to 8K@60Hz and 4K@144Hz using DSC for exceptional image quality.
- - Double shielded cable corrosion-resistant 32AWG Copper conductors.
- - Requires DisplayPort Alternate Mode support by the USB Port/Bus

The Lindy Bi-Directional USB Type-C to DisplayPort Cable is the ideal solution for hot-swapping display units or source devices. Designed to deliver reliable and consistent resolutions up to 8K (7680x4320@60Hz) using DSC (Display Stream Compression), it ensures stunning visuals without compromising quality, offering exceptional performance, corrosion resistance, and long-lasting durability.

Due to its Bi-directional capability, this versatile cable supports both USB Type-C and DisplayPort displays and source devices, providing maximum flexibility for any display configuration. It is perfect for on-the-go meetings, hot-desking environments, and home office setups where fast connectivity and high-quality visuals are essential. Perfect for classrooms, training rooms, multimedia installations, and creative workflows making it easy to swap between different devices and displays.

With its robust build and high-resolution capabilities, this cable ensures crystal-clear visuals for presentations, content sharing, and immersive viewing experiences.

The Lindy Bi-Directional USB Type C to DisplayPort cable is available in lengths from 1m to 2m.

- Connectors
- PConnector A: USB Type C Male
- Connector B: DisplayPort Male

> Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)

Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)

- Housing Material: Aluminium
- Connector Plating: Gold Plating
- Pin Construction: Copper Alloy
- Pin Plating: Nickel
- Dimensions (approx.) WxDxH:
- DisplayPort: 21.0x38.9x13.6mm (0.83x1.53x0.54in)
- USB Type C: 30x10x5mm (1.80x0.39x0.2in)

• Cable Construction

- Length: 1m (3.28ft)
- Standard: DisplayPort 1.4
- Colour: Grey
- Type: Round
- Jacket Diameter: 4.5mm (0.17in)
- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge: 32AWG

• Specifications

- Supported Bandwidth: 32.4Gbps
- Maximum Resolution: 7680x4320@60Hz
- Power Delivery: N/A
- Nominal Attenuation:
- 300kHz-825MHz -
- 825MHz-2.475GHz -
- 2.475GHz-4.125GHz -
- 4.125GHz-5.1GHz -
- Minimum Bend Radius: 48mm (1.89in)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)

• Miscellaneous

- Packaging Type: Polybag
- Product Compliance: CE, FCC, RoHS, REACH, California Proposition 65

• This product is also available in other lengths

- 1m (3.28ft) - 43503
- 2m (6.56ft) - 43504

> Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)

Cabo USB-C <> DP 01.0m 8K60 Bi-Directional LINDY (43503)

Este artigo foi introduzido no catalogo online : Friday, 17 April 2026

LIDERTRONICA - Um Mundo de Acessórios para Informática