Cabo XLR 01.00m M/F LINDY (35701)

Referencia : 35701

Cabo XLR 01.00m M/F LINDY (35701)

Fabricante : Lindy

XLR Male to XLR Female Audio Cable, 1m, Black
External Line Return Male to Female Audio Cable

• Ensures clear and consistent signal transfer between microphones, mixers, and other XLR-equipped devices • Robust metal connectors • Ideal for live sound, studio setups, corporate AV, and fixed installations • Aluminium Mylar Shielding to protect against electrical interference

The Lindy XLR Male to XLR Female Cable offers a reliable and high-quality connection between microphones, mixers, interfaces, and other audio equipment. It delivers clear signal transfer for everyday use in professional environments such as studios, live events, and corporate AV installations.

Featuring robust connectors and durable construction, this cable is built to handle regular setup and use while maintaining consistent performance. It is ideal for extending existing XLR runs or linking audio devices within racks, technical furniture, or stage setups.

Whether you are installing a sound system, building AV infrastructure, or managing digital signage, this cable provides dependable performance you can trust.

Please note: For the best results, avoid sharp bends and keep the cable clear of potential interference sources.

The Lindy XLR Male to XLR Female cable is available in lengths from 1m - 10m.

LIDERTRÃ“NICA - Um Mundo de Acessórios para InformÃ¡tica

Cabo XLR 01.00m M/F LINDY (35701)

Cabo XLR 01.00m M/F LINDY (35701)

LIDERTRÃ“NICA - Um Mundo de Acessórios para InformÃ¡tica

Technical details

• Connectors

• Connector A: XLR Male • Connector B: XLR Female • Housing Material: Aluminium • Connector Plating: Nickel Plated • Pin Construction: Nickel • Pin Plating: Nickel • Dimensions (approx.) WxDxH: 17x16x30mm (0.66x0.62x1.18in)

• Cable Construction

• Length: 1m (3.28ft) • Colour: Black • Type: Round • Jacket Diameter: 6mm (0.23in) • Jacket Material: TPE • Conductor Material: Bare Copper • Conductor Gauge: 26AWG • Shielding: Aluminium Mylar 80%

• Specifications

• Nominal Attenuation: < 0.3 dB per 100m at 1 MHz • Minimum Bend Radius: 50mm (1.97in) • Operating Temperature: -20Â°C to 70Â°C (-4Â°F to 158Â°F) • Storage Temperature: -40Â°C to 80Â°C (-40Â°F to 176Â°F)

• Miscellaneous

• Packaging Type: Polybag • Certificated: RoHS, REACH

• This product is also available in other lengths

• 35701 - 1m (3.28ft) • 35702 - 2m (6.56ft) • 35703 - 3m (9.84ft) • 35704 - 5m (16.4ft) • 35705 - 7.5m (24.60ft) • 35706 - 10m (32.81ft)

Este artigo foi introduzido no catalogo online : Thursday, 22 October 2026